

25m Adjustable Horizontal Lifeline 4 Man System

Features

- Light Weight quick and easy to install, reusable Horizontal lifeline system.
- 4 Steel O-Rings to enable the user to easily attach the Lanyard of his Harness to the Lifeline using a Connector.
- Has 2 Cross Arm Straps each to tie off to the structure where the anchorage is required.
- Has unique tension indicator for creating an adequate tension in the line. Once the required tension is achieved, the disc on the tension indicator rotates freely, indicating the line is ready to use.
- Has Swivel Connector- specially designed to prevent any twisting of the rope.
- Supplied with 2 x 1.5m Anchor straps AFA920115(1.5M)
- Suitable for upto 4 users

How To Use

Refer to User Instruction Manual



Material

Rope Line	:	16 mm Kernmantle Rope
Tensioner	:	Aluminum Alloy & Stainless Steel
O Rings	:	Forged Alloy Steel
	:	MBS 23kN
Karabiners	:	Galvanized Steel
	:	MBS 40kN
Cross Arm Strap	:	Polyester 44mm, MBS 25kN



System Strength and Span

Minimum Breaking Strength: 25kN

Minimum Span: 5m

Maximum Span: 25m

Weight

9.28 kgs \pm 0.10 kgs

Relevant Standards

EN 795:2012 TYPE C & TS 16415:2013 TYPE C

